


JIS B 1176:2014



ねじの呼び			d		M1.6		M2		M2.5		M3		M4		M5		M6		M8		M10		M12		(M14)		M16		(M18)		M20				
ねじのピッチ P			並目		0.35		0.4		0.45		0.5		0.7		0.8		1.0		1.25		1.5		1.75		2.0		2.0		2.5		2.5				
			細目																1.0		1.25		1.25		1.5		1.5				1.5				
b ¹⁾			参考		15		16		17		18		20		22		24		28		32		36		40		44		48		52				
dk			最大 ²⁾ (基準寸法)		3.00		3.80		4.50		5.50		7.00		8.50		10.00		13.00		16.00		18.00		21.00		24.00		27.00		30.00				
			最大 ³⁾		3.14		3.98		4.68		5.68		7.22		8.72		10.22		13.27		16.27		18.27		21.33		24.33		27.33		30.33				
			最小		2.86		3.62		4.32		5.32		6.78		8.28		9.78		12.73		15.73		17.73		20.67		23.67		26.67		29.67				
da			最大		2		2.6		3.1		3.6		4.7		5.7		6.8		9.2		11.2		13.7		15.7		17.7		20.2		22.4				
ds			最大 (基準寸法)		1.60		2.00		2.50		3.00		4.00		5.00		6.00		8.00		10.00		12.00		14.00		16.00		18.00		20.00				
			最小		1.46		1.86		2.36		2.86		3.82		4.82		5.82		7.78		9.78		11.73		13.73		15.73		17.33		19.67				
e ⁴⁾⁵⁾			最小		1.733		1.733		2.303		2.873		3.443		4.583		5.723		6.863		9.149		11.429		13.716		15.996		16.00		19.437				
lf			最大		0.34		0.51		0.51		0.51		0.6		0.6		0.68		1.02		1.02		1.45		1.45		1.45		1.87		2.04				
k			最大 (基準寸法)		1.60		2.00		2.50		3.00		4.00		5.00		6.0		8.00		10.00		12.00		14.00		16.00		18.00		20.00				
			最小		1.46		1.86		2.36		2.86		3.82		4.82		5.7		7.64		9.64		11.57		13.57		15.57		17.57		19.48				
r			最小		0.1		0.1		0.1		0.1		0.2		0.2		0.25		0.4		0.4		0.6		0.6		0.6		0.6		0.8				
s ⁵⁾			呼び		1.5		1.5		2		2.5		3		4		5		6		8		10		12		14		14		17				
			許容差		+0.08		+0.08		+0.08		+0.08		+0.08		+0.08		+0.095		+0.14		+0.14		+0.175		+0.175		+0.212		+0.212		+0.212		+0.23		
					+0.02		+0.02		+0.02		+0.02		+0.02		+0.020		+0.02		+0.02		+0.025		+0.025		+0.025		+0.032		+0.032		+0.032		+0.05		
t			最小		0.7		1		1.1		1.3		2		2.5		3		4		5		6		7		8		9		10				
v			最大		0.16		0.2		0.25		0.3		0.4		0.5		0.6		0.8		1		1.2		1.4		1.6		1.8		2				
dw			最小		2.72		3.48		4.18		5.07		6.53		8.03		9.38		12.33		15.33		17.23		20.17		23.17		25.87		28.87				
w			最小		0.55		0.55		0.85		1.15		1.4		1.9		2.3		3.3		4		4.8		5.8		6.8		7.7		8.6				
ねじの呼び			d		M1.6		M2		M2.5		M3		M4		M5		M6		M8		M10		M12		(M14)		M16		(M18)		M20				
呼び長さ			最小		最大		最小		最大		最小		最大		最小		最大		最小		最大		最小		最大		最小		最大		最小		最大		
2.5	2.30	2.70																																	
3	2.80	3.20																																	
4	3.76	4.24																																	
5	4.76	5.24																																	
6	5.76	6.24																																	
8	7.71	8.29																																	
10	9.71	10.29																																	
12	11.65	12.35																																	
16	15.65	16.35																																	
20	19.58	20.42				2	4																												
25	24.58	25.42						5.75	8	4.5	7																								
30	29.58	30.42								9.5	12	6.5	10	4	8																				
35	34.5	35.5										11.5	15	9	13	6	11																		
40	39.5	40.5										16.5	20	14	18	11	16	5.75	12																
45	44.5	45.5												19	23	16	21	10.75	17	5.5	13														
50	49.5	50.5												24	28	21	26	15.75	22	10.5	18														
55	54.4	55.6														26	31	20.75	27	15.5	23	10.25	19												
60	59.4	60.6														31	36	25.75	32	20.5	28	15.25	24	10	20										
65	64.4	65.6																30.75	37	25.5	33	20.25	29	15	25	11	21	4.5	17						
70	69.4	70.6																		35.75	42	30.5	38	25.25	34	20	30	16	26	9.5	22				
80	79.4	80.6																		45.75	52	40.5	48	35.25	44	30	40	26	36	19.5	32	15.5	28		
90	89.3	90.7																				50.5	58	45.25	54	40	50	36	46	29.5	42	25.5	38		
100	99.3	100.7																				60.5	68	55.25	64	50	60	46	56	39.5	52	35.5	48		
110	109.3	110.7																						65.25	74	60	70	56	66	49.5	62	45.5	58		
120	119.3	120.7																						75.25	84	70	80	66	76	59.5	72	55.5	68		
130	129.2	130.8																								80	90	76	86	69.5	82	65.5	78		
140	139.2	140.8																								90	100	86	96	79.5	92	75.5	88		
150	149.2	150.8																										96	105	89.5	102	85.5	98		
160	159.2	160.8																										106	116	99.5	112	95.5	108		
180	179.2	180.8																													119.5	132	115.5	128	
200	199.1	200.9																													139.5	152	135.5	148	